



Main Specification				Image space NA	
Magnification	0.43X	0.5X	0.57X	Object space NA	0.04
Working Distance	437.5±5	390.66±5	354±5	Entrance pupil diameter	$\phi 33$
Conjugate Distance	674±9	636.99±9	611±9	Entrance pupil position	58
Flange Focal Distance	181±0.5	192.71±0.5	202±0.5	Exit pupil diameter	$\phi 31$
Max image circle	$\phi 82$			Exit pupil position	-212
F/#	4.0-16				
EFL	120				
Distortion	0.002%				
IMAGE QUALITY					
AXIS	$\phi 46.2$	$\phi 66$	$\phi 82$		
200lp/mm	160lp/mm	125lp/mm	125lp/mm		

注：
Logo上的圆点粘贴位置与成像面垂直为最佳成像点。

TOLERANCE: LINEARITY TOLERANCES ±0.05 ANGULAR TOLERANCES ARE ±30° DRAFT ANGLES AREA ±0.5°/SIDE			三角法 	材料(环保)	单位	比例
设计	朱周德	2015-05-05	名称	LS1605B技术规格图	mm	1:1
校对			代号	LS1605B-SPEC		页码
审核						1/1
批准						版本
标记	处数	更改文件号	担当	变更日期		V0